

20' Containerized Dewatering and Waste Oil Treatment System

System Features



Dedicated Polymer Tanks with Top Mounted Agitators and Injection Pumps



Exterior Screw Conveyor for Solids Discharge



Cabinet Enclosure with Integrated Touch Screen Human Machine Interface (HMI)



Dedicated Progressive Cavity Feed Pump

As industry environmental regulations continue to become more stringent, having the right solids control and dewatering equipment has become vital to operations. Dewatering presents a great deal of benefits and advantages. One such benefit includes discharge compliance, in which many cases result in a "zero-discharge" or "closed-loop system." In addition, the importance of



recovering oil from waste is vital to maximizing profits. With the correct combination of chemicals, effective removal of solids, while recovering high quality oil and water, can be achieved.

Dewatering also maximizes drilling fluid recovery, ultimately lowering overall mud costs as well as disposal and transportation expenses. Furthermore, these systems improve rate of penetration. With a "zero-discharge" or "closed-loop system," operations can operate without open pits, therefore reducing the location footprint and environmental impact.

For over 25 years, Elgin has been designing solids management and dewatering systems for the most demanding environments. With this experience, Elgin has

designed a variety of Containerized
Dewatering Units. These units
are designed with the customer in
mind by being mobile and compact.
Furthermore, they also incorporate
sophisticated graphical user interfaces,
chemical additive injection systems,
ESS-1450HD2 or ESS-1655HD2 decanter
centrifuge, and in-line mixing systems.
By utilizing proprietary polymer
hydration manifolds, the polymer
enhanced flocculation of colloidal and
ultra-fine drilled solids can be efficiently
removed with a decanter centrifuge.

This versatile unit can be customized by our engineering team to meet any specific needs or challenges. It may be operated as a stand-alone device or can be incorporated as the cornerstone of



a sophisticated closed-loop solids control and waste management treatment system. Systems can be climate controlled and insulated, upon request.











20' Containerized Dewatering and Waste Oil Treatment System



ESS-1450HD2 Centrifuge

Elgin's ESS-1450HD2 is fitted with a NEMA premium, continuous duty, energy-efficient, poly-chain driven, 50 hp main drive. The 50 hp main drive can operate the centrifuge up to a maximum rotational speed of 3,250 rpm, thus, generating more than 2,100 G's of force.



Select Floc™ Polymer Conditioning System

By using existing equipment at the rig, the Select Floc™ allows customers to optimize existing assets, while incorporating the advances of Elgin's polymer make-down and feed systems to createon-site dewatering.

Overview of Unit Features:

- Compact design for small footprint.
- 200 gpm progressive cavity feed pump for homogonous feed.
- ESS-1450HD2 or ESS-1655HD2 decanter centrifuge capable of producing 2,100 G's of force.
- 12" shafted screw conveyor for easy cuttings discharge.
- Easy to use VFD HMI control panel with touch screen interface.
- Top mounted polymer tank agitators.
- Integrated plumbing to achieve hydration residence time.

| Model Number: | ESS-DW-20 |
|---------------------------------|---|
| Description: | 20' HMI Containerized Dewatering Unit |
| Length: | 20' (6.1m) |
| Width: | 8' (2.4m) |
| Height: | 9.5' (2.9m) |
| Centrifuge (rpm / G's): | ESS-1450HD2 (3,200 / 2,000) |
| Coagulant Tank: | 2 qty. 160 gallon (606 liter) |
| Flocculant Tank: | 2 qty. 330 gallon (1,250 liter) |
| Dissolution / Transfer Tank: | 460 gallon (1,750 liter) |
| Tank Agitators: | 4 x 1 hp |
| Electrical: | 380V / 50Hz or 460V / 60Hz – 3 Phase |

| ESS-1450HD2 Centrifuge | |
|------------------------|--|
| Equipment Image: | ELGIN |
| Maximum G-Force: | 2,100 |
| Maximum Speed: | 3,250 rpm |
| Capacity: | 200 gpm (12.6 lps) |
| Bowl Construction: | 304 or 316 Stainless Steel |
| Bowl Diameter: | 14" (356 mm) |
| Bowl Length: | 49.5" (1,257 mm) |
| Weight: | 6,583 lbs (2,986 kgs) |
| Skid Dimensions: | 103" (2,616 mm) L x 75" (1,905 mm) W x 48" (1,219 mm) |
| Gearbox Ratio: | 52:1 or 125:1 |

Chemically Enhanced Mechanical Separation

By combining expertise in both dewatering polymers and solid/liquid separation technologies, Elgin has developed an organization capable of providing complex chemically-enhanced mechanical separation solutions. As a service oriented organization, Elgin's focus is on providing timely value. This value is further enhanced when customers take advantage of Elgin's integration, modularization, and customization capabilities. Elgin will continue to be an industry leader in bringing mobile and/or modular turn-key solutions to the industry's toughest fluid management problems.





